


R C M T



Shape




Clearance Angle



Tolerance



$s \pm 0.13$
For $l = 06/08/10$, $d \pm 0.05$ $m \pm 0.08$
For $l = 12$, $d \pm 0.08$ $m \pm 0.13$




Fixing Chip breaker

Insert Designation	Grade	l	s	r	Catalog Nr.
RCMT 0602 M0	LT 1000	06	2.38	3	T0001914
RCMT 0803 M0	LT 1000	08	3.18	4	T0001915
RCMT 10T3 M0	LT 1000	10	3.97	5	T0001916
RCMT 1204 M0	LT 1000	12	4.76	6	T0001917

Round inserts with positive Rake angle and excellent edge resistance. Suitable for Profiling operations of Mill rolls and Aerospace parts.

Application Guide

	Finishing	Medium	Roughing / Interrupted cut	
RCMT 0602	☹️	😊	☹️	<p>😊 = Good ☹️ = Acceptable ☹️ = Not recommended</p> <p>Finishing: d.o.c. = 0.30 - 1.50 mm fn = 0.08 - 0.20 mm/rev</p> <p>Medium: d.o.c. = 0.70 - 4.50 mm fn = 0.15 - 0.45 mm/rev</p> <p>Roughing d.o.c. = 3.00 - 7.00 mm fn = 0.35 - 0.70 mm/rev</p>
RCMT 0803	☹️	😊	☹️	
RCMT 10T3	☹️	😊	☹️	
RCMT 1204	☹️	😊	☹️	



Machine Recommendations Guide
Details on page 10

RCMT 0803 M0 LT 10 & LT 1000

Material Group	Gr. N°	VDI Group	Material Examples*	Hardness	D.O.C. [mm]		Feed [mm/rev]		Amax [mm ²]	V _c [m/min]		Optimal cutting conditions				
					min	max	min	max		min	max	D.O.C.	Feed	V _c		
Steel	Non-alloyed	1	C35, Ck45, 1020,	125 HB	0.5	2.4	0.15	0.40	0.77	180	330	1.2	0.35	240		
		2	1045, 1060,	190 HB		2.4		0.40	0.77		280		0.35	220		
		3	28Mn6	250 HB		1.8		0.35	0.67		250		0.30	200		
	Low alloyed	2	6	42CrMo4, St50, Ck60, 4140, 4340, 100Cr6	180 HB	0.5	2.4	0.15	0.35	0.67	120	280	1.2	0.30	200	
		4,6	230 HB		2.4		0.35		0.58	250		180				
		5,7	280 HB		2.4		0.35		0.48	210		150				
		8	350 HB		1.8		0.35		0.43	180		130				
	High alloyed	3	10	X40CrMoV5, H13, M42, D3, S6-5-2, 12Ni19	220 HB	0.5	2.4	0.13	0.35	0.58	70	190	1.2	0.30	140	
		10	280 HB		2.4		0.30		0.48	150		0.28		120		
		11	320 HB		1.8		0.30		0.38	130		0.28		100		
		11	350 HB		1.8		0.30		0.31	110		0.28		90		
Stainless Steel	Austenitic	4	304, 316, X5CrNi18-9	180 HB	0.5	2.4	0.14	0.35	0.38	170	270	1.2	0.32	220		
		14		240 HB		2.4		0.32	0.38		160			220	190	
	Duplex	5	X2CrNi23-4, S31500	290 HB	0.5	1.8	0.13	0.30	0.36	80	150	1.2	0.28	100		
		14		310 HB		1.8		0.30	0.36		70			140	90	
	Ferritic & Martensitic	6	410, X6Cr17, 17-4 PH, 430	200 HB	0.5	2.4	0.15	0.35	0.38	170	250	1.2	0.32	210		
		13		42 HRc		2.4		0.30	0.36		120			190	0.28	140
Cast Iron	Grey	7	GG20, GG40, EN-GJL-250, No30B	150 HB	0.5	2.4	0.11	0.45	0.84	170	250	1.2	0.35	200		
		15		200 HB		2.4		0.45	0.78		160			230	180	
		16		250 HB		2.4		0.45	0.72		150			210	160	
	Malleable & Nodular	8	GGG40, GGG70, 50005	150 HB	0.5	2.4	0.11	0.35	0.72	120	250	1.2	0.30	180		
		17,19		200 HB		2.4		0.35	0.60		230			160		
		18,20		250 HB		2.4		0.35	0.54		190			140		
High Temp. Alloys	Fe, Ni & Co based	9	Incoloy 800	240 HB	0.5	1.8	0.13	0.30	0.36	25	50	1.2	0.28	33		
		33		Inconel 700		250 HB		1.8	0.30		0.36			25	50	30
		34		Stellite 21		350 HB		1.8	0.30		0.36			23	45	28
	Ti based	10	TiAl6V4 T40	-	0.5	1.8	0.13	0.32	0.38	45	65	1.2	0.30	55		
37		-		1.8		0.30		0.36	35		60			0.28	45	
Hardened Mat.	Steel	11	X100CrMo13, 440C, G-X260NiCr42	45 HRc	0.5	1.4	0.05	0.22	0.24	50	100	1.1	0.18	80		
		38		50 HRc	0.5	1.2		0.18	0.20	40	90	0.8	0.16	70		
		38		55 HRc	0.3	1.0		0.14	0.14	40	80	0.7	0.12	60		
	Chilled Cast Iron	40	Ni-Hard 2	400 HB	0.5	1.4	0.05	0.22	0.20	40	60	1.1	0.18	50		
	White Cast Iron	41	G-X300CrMo15	55 HRc	0.3	1.0	0.05	0.14	0.12	30	50	0.7	0.12	40		
NF	Al (>8%Si)	12	25	AlSi12	130 HB	0.5	2.4	0.15	0.40	0.84	200	400	1.2	0.35	280	