


HSS SINGLE FLUTE CHAMFERING CUTTERS

HSS EINSCHNEIDEN KEGELSENKER

- ▶ For wood and hard plastics.
- ▶ Can drill in sheet materials.
- ▶ Easy to resharpen.
- ▶ Works without vibrations.

- ▶ Für Holz und Hartplastik
- ▶ Kann in Bleche bohren
- ▶ Leicht nachzuschärfen
- ▶ Arbeitet ohne Vibration






Unit : mm

EDP No. (uncoating)			Angle α (-1°)	Nominal Diameter D1	Shank Diameter D2	Overall Length L(±1)	Capacity min/max
HSSCo8	HSS-E	HSS					
C1119100	C2119100	C3119100	90°	10.0	6	45	1 - 10
C1119150	C2119150	C3119150	90°	15.0	8	55	2 - 15
C1119200	C2119200	C3119200	90°	20.0	10	65	2 - 20
C1119250	C2119250	C3119250	90°	25.0	12	78	3 - 25
C1119300	C2119300	C3119300	90°	30.0	12	88	3 - 30
C1119350	C2119350	C3119350	90°	35.0	16	110	4 - 35
C1119400	C2119400	C3119400	90°	40.0	16	115	5 - 40
C1119450	C2119450	C3119450	90°	45.0	16	120	10 - 45
C1119500	C2119500	C3119500	90°	50.0	16	130	12 - 50

▶ TiN & TiCN coating are available on your request.

Nominal Dia Tolerance(mm)	Shank Dia. Tolerance(mm)
+0.3	h9



Material	V	S			V	S			V	S		
		Ø ≤ 10	Ø ≤ 20	Ø ≤ 30		Ø ≤ 10	Ø ≤ 20	Ø ≤ 30		Ø ≤ 10	Ø ≤ 20	Ø ≤ 30
STEELS ≤ 500N/mm ²	35-45	0.20	0.22	0.24	35-45	0.20	0.22	0.24	17-22	0.30	0.32	0.36
STEELS 500~800N/mm ²	20-30	0.14	0.17	0.20	20-30	0.14	0.17	0.20	10-15	0.28	0.30	0.31
STEELS 800~1000N/mm ²	15-20	0.11	0.12	0.14	15-20	0.11	0.12	0.14	8-12	0.24	0.26	0.28
STEELS-STAINLESS STEEL 1000~1300N/mm ²	12-15	0.10	0.12	0.15	12-15	0.10	0.12	0.15	6-8	0.20	0.20	0.22
STAINLESS STEELS	6-8	0.07	0.08	0.09	6-8	0.07	0.08	0.09	4-6	0.08	0.09	0.10
CAST IRON	20-40	0.15	0.24	0.28	20-40	0.15	0.24	0.28	15-25	0.13	0.19	0.24
ALUMINUM	50-60	0.22	0.25	0.27	50-60	0.22	0.25	0.27	35-45	0.27	0.30	0.35
BRASS-BRONZE	30-40	0.23	0.25	0.28	30-40	0.23	0.25	0.28	20-30	0.30	0.30	0.31
COPPER	20-30	0.22	0.25	0.27	20-30	0.22	0.25	0.27	10-15	0.29	0.30	0.31
PLASTICS	50-100	0.50	0.60	0.65	50-100	0.50	0.60	0.65	35-70	0.40	0.45	0.50

V : Cutting Speed(mm/min)

S : Feed per Revolution(mm/rev)