



WORM PATTERN DRILLS

DL510 SERIES

HSS-E, STRAIGHT SHANK TWIST DRILLS for DEEP HOLES *STUB* HSS-E, SPIRALBOHRER für TIEFLOCH mit ZYLINDERSCHAFT *EXTRA KURZ*

► **Application** : Drilling deep holes in non alloy steels, alloy steels, grey cast iron, malleable cast iron, special aluminum or magnesium alloys.

► **Verwendung** : Zum Bohren von legiertem und unlegiertem stahl, Grauguß, Temperguß, Sphäroguß, Druckguß, Alu-Legierungen kurzspanend, Bronze, Messing zäh, Neusilber.



► **DH100**
worm pattern drills

Unit : mm

EDP No.	Drill Diameter	Flute Length	Overall Length	EDP No.	Drill Diameter	Flute Length	Overall Length
	D1	L1	L2		D1	L1	L2
DL510020	2.0	12	38	DL510047	4.7	24	58
DL510021	2.1	12	38	DL510048	4.8	26	62
DL510022	2.2	13	40	DL510049	4.9	26	62
DL510023	2.3	13	40	DL510050	5.0	26	62
DL510024	2.4	14	43	DL510051	5.1	26	62
DL510025	2.5	14	43	DL510052	5.2	26	62
DL510026	2.6	14	43	DL510053	5.3	26	66
DL510027	2.7	16	46	DL510054	5.4	28	66
DL510028	2.8	16	46	DL510055	5.5	28	66
DL510029	2.9	16	46	DL510056	5.6	28	66
DL510030	3.0	16	46	DL510057	5.7	28	66
DL510031	3.1	18	49	DL510058	5.8	28	66
DL510032	3.2	18	49	DL510059	5.9	28	66
DL510033	3.3	18	49	DL510060	6.0	28	66
DL510034	3.4	20	52	DL510061	6.1	31	70
DL510035	3.5	20	52	DL510062	6.2	31	70
DL510036	3.6	20	52	DL510063	6.3	31	70
DL510037	3.7	20	52	DL510064	6.4	31	70
DL510038	3.8	22	55	DL510065	6.5	31	70
DL510039	3.9	22	55	DL510066	6.6	31	70
DL510040	4.0	22	55	DL510067	6.7	31	70
DL510041	4.1	22	55	DL510068	6.8	34	74
DL510042	4.2	22	55	DL510069	6.9	34	74
DL510043	4.3	24	58	DL510070	7.0	34	74
DL510044	4.4	24	58	DL510071	7.1	34	74
DL510045	4.5	24	58	DL510072	7.2	34	74
DL510046	4.6	24	58	DL510073	7.3	34	74

◎ : Excellent ○ : Good

Carbon Steels	Alloy Steels	Prehardened Steels	Hardened Steels		Cast Iron	Aluminum	Stainless Steels	Titanium	Mild Steels	Copper	Bronze
~HB225	HB225~325	HRc30~45	HRc45~55	HRc55~							
◎	◎				○	○			○		



WORM PATTERN DRILLS

DL510 SERIES

HSS-E, STRAIGHT SHANK TWIST DRILLS for DEEP HOLES *STUB*

STUB

HSS-E, SPIRALBOHRER für TIEFLOCH mit ZYLINDERSCHAFT *EXTRA KURZ*

EXTRA KURZ

► **Application** : Drilling deep holes in non alloy steels, alloy steels, grey cast iron, malleable cast iron, special aluminum or magnesium alloys.

► **Verwendung** : Zum Bohren von legiertem und unlegiertem stahl, Grauguß, Temperguß, Sphäroguß, Druckguß, Alu-Legierungen kurzspanend, Bronze, Messing zäh, Neusilber.



► **DH100** worm pattern drills

Unit : mm

EDP No.	Drill Diameter	Flute Length L1	Overall Length L2	EDP No.	Drill Diameter	Flute Length L1	Overall Length L2
	D1				D1		
DL510074	7.4	34	74	DL510100	10.0	43	89
DL510075	7.5	34	74	DL510102	10.2	43	89
DL510076	7.6	37	79	DL510105	10.5	43	89
DL510077	7.7	37	79	DL510108	10.8	47	95
DL510078	7.8	37	79	DL510110	11.0	47	95
DL510079	7.9	37	79	DL510112	11.2	47	95
DL510080	8.0	37	79	DL510115	11.5	47	95
DL510081	8.1	37	79	DL510118	11.8	47	95
DL510082	8.2	37	79	DL510120	12.0	51	102
DL510083	8.3	37	79	DL510125	12.5	51	102
DL510084	8.4	37	79	DL510130	13.0	51	102
DL510085	8.5	37	79	DL510135	13.5	54	107
DL510086	8.6	40	84	DL510140	14.0	54	107
DL510087	8.7	40	84	DL510145	14.5	56	111
DL510088	8.8	40	84	DL510150	15.0	56	111
DL510089	8.9	40	84	DL510155	15.5	58	115
DL510090	9.0	40	84	DL510160	16.0	58	115
DL510091	9.1	40	84	DL510165	16.5	60	119
DL510092	9.2	40	84	DL510170	17.0	60	119
DL510093	9.3	40	84	DL510175	17.5	62	123
DL510094	9.4	40	84	DL510180	18.0	62	123
DL510095	9.5	40	84	DL510185	18.5	64	127
DL510096	9.6	43	89	DL510190	19.0	64	127
DL510097	9.7	43	89	DL510195	19.5	66	131
DL510098	9.8	43	89	DL510200	20.0	66	131
DL510099	9.9	43	89				

◎ : Excellent ○ : Good

Carbon Steels	Alloy Steels	Prehardened Steels	Hardened Steels		Cast Iron	Aluminum	Stainless Steels	Titanium	Mild Steels	Copper	Bronze
~HB225	HB225~325	HRc30~45	HRc45~55	HRc55~							
◎	◎				○	○			○		



WORM PATTERN DRILLS

RECOMMENDED CUTTING CONDITIONS EMPFOHLENE SCHNEIDKONDITIONEN

HSS-E, DH100 TYPE WORM PATTERN DRILLS, DIN1897, DIN338, DIN340, DIN1869, DIN341, DIN1870
HSS-E, DH100 TYPE WORM PATTERN SPIRALBOHRER, DIN1897, DIN 338, DIN 340, DIN 1869, DIN 341, DIN 1870

DL510, DL508, DL509, DL505, DL504, DL600, DL608, DL609, DL610 SERIES

Unit : mm

WORK MATERIAL	CARBON STEELS ALLOY STEELS		TOOL STEELS HARDENED STEELS		SOFT GREY CAST IRON		HARD GREY CAST IRON	
	HRc15 ~ 30		HRc20 ~ 40					
HARDNESS	700 ~ 1000 N/mm ²		800 ~ 1200 N/mm ²					
STRENGTH								
DIAMETER	N	S	N	S	N	S	N	S
2.0	2630	0.03	2100	0.025	4200	0.06	1680	0.05
2.5	2100	0.04	1680	0.03	3300	0.08	1310	0.06
3.0	1680	0.05	1310	0.04	2630	0.10	1050	0.08
4.0	1310	0.06	1050	0.05	2100	0.13	840	0.10
5.0	1050	0.06	840	0.05	1680	0.13	660	0.10
6.0	840	0.08	660	0.06	1310	0.16	530	0.13
8.0	660	0.10	530	0.08	1050	0.20	420	0.17
10.0	530	0.13	420	0.10	840	0.25	330	0.21
13.0	420	0.13	330	0.10	660	0.25	260	0.21
16.0	330	0.15	260	0.13	530	0.30	210	0.25
20.0	260	0.20	210	0.15	420	0.40	170	0.30
25.0	210	0.25	170	0.20	330	0.50	130	0.50
30.0	170	0.25	130	0.20	260	0.50	110	0.50

N = R.P.M

S = Feed per Revolution (mm/rev.)

HSS-E, DH50 TYPE WORM PATTERN DRILLS HSS-E, DH50 TYPE WORM PATTERN SPIRALBOHRER

DL507 SERIES

Unit : mm

WORK MATERIAL	CARBON STEELS ALLOY STEELS		SOFT GREY CAST IRON		ALUMINUM ALLOY	
	HRc15 ~ 30					
HARDNESS	700 ~ 1000 N/mm ²					
STRENGTH						
DIAMETER	N	S	N	S	N	S
2.0	2630	0.03	4200	0.06	8700	0.04
2.5	2100	0.04	3300	0.08	6950	0.05
3.0	1680	0.05	2630	0.10	5800	0.06
4.0	1310	0.06	2100	0.13	4300	0.08
5.0	1050	0.06	1680	0.13	3500	0.10
6.0	840	0.08	1310	0.16	2900	0.12
8.0	660	0.10	1050	0.20	2200	0.16
10.0	530	0.13	840	0.25	1750	0.20
13.0	420	0.13	660	0.25	1350	0.26

N = R.P.M

S = Feed per Revolution (mm/rev.)