





## CZD-24 HSS

INDEX Z1-024011-0000









ZAWARTOŚĆ CONTENTS INHALT	Gwintowniki Taps Gewindebohrer	Narzynki Screwing dies Schneideisen	Pokrętka do gwintowników Tap wrench verstellbare Windeisen	Oprawka do narzynek Die stock Schneideisenhalter
	ISO-529/2 HSS	DIN-EN 22 568 HSS 800	PBPc	PBGa
				
M3, M4, M5, M6, M8, M10, M12	Ø25 x 9: M3, M4, M5, M6, M8; M10, M12	Nr 2 zm.: 2,5 ÷ 9 mm	Ø25 x 9 mm	
WYMIARY DIMENSIONS ABMESSUNGEN	290 x 180 x 33 mm			
CIEŻAR WEIGHT GEWICHT	1,25 kg			

## CZD-40 HSS

INDEX Z1-040011-0000



ZAWARTOŚĆ CONTENTS INHALT	Gwintowniki Taps Gewindebohrer	Narzynki Screwing dies Schneideisen	Wzorec zarysu gwintu Screw pitch gauge Gewindeprofil-Lehre	Pokrętki do gwintowników Tap wrenches verstellbare Windeisen	Oprawki do narzynek Die stocks Schneideisenhalter	Wkrętak Screwdriver Schraubenzieher
	ISO-529/2 HSS dla M3+M12 DIN-352/2 HSS dla M14+M20	DIN-EN 22 568 HSS 800	MWGa	PBPc	PBGa	RWWe
						
M3, M4, M5, M6, M7, M8, M10, M12, M14, M16, M20	Ø25 x 9: M3, M4, M5, M6, M7, M8, M10 Ø38 x 14: M12, M14, M16, M20	0,4 ÷ 6 mm	Nr 2 zm.: 2,5 ÷ 9 mm Nr 3: 4,9 ÷ 14 mm	Ø25 x 9 mm Ø38 x 14 mm	4 x 90 mm	
WYMIARY DIMENSIONS ABMESSUNGEN	475 x 255 x 40 mm					
CIEŻAR WEIGHT GEWICHT	3,40 kg					