


CARBIDE, 4 FLUTE LONG REACH CORNER RADIUS

VOLLHARTMETALL, 4 SCHNEIDEN GROÖE REICHWEITE ECKENRADIUS

- Suitable for dry milling applications at high temperatures.
- Excellent high-performance end mills.
- Designed for milling of radius bottom slots, fillets and special contours.

- Für die Trockenbearbeitung.
- Hervorragendes Preis - Leistungsverhältnis.
- Bestimmt für das Fräsen von Nuten mit konvexem Grund, Sonderprofilen und zum Kopieren.



P.826

Unit : mm

EDP No.	Corner Radius R	Mill Diameter	Shank Diameter	Length of Cut	Overall Length
G9B85030	R0.5	3.0	4	6	75
G9B85901	R1.0	3.0	4	6	75
G9B85040	R0.5	4.0	4	8	75
G9B85902	R1.0	4.0	4	8	75
G9B85050	R0.5	5.0	6	10	75
G9B85903	R1.0	5.0	6	10	75
G9B85060	R0.5	6.0	6	12	75
G9B85904	R1.0	6.0	6	12	75
G9B85080	R0.5	8.0	8	16	100
G9B85905	R1.0	8.0	8	16	100
G9B85906	R1.5	8.0	8	16	100
G9B85907	R2.0	8.0	8	16	100
G9B85908	R2.5	8.0	8	16	100
G9B85100	R0.5	10.0	10	20	100
G9B85909	R1.0	10.0	10	20	100
G9B85910	R1.5	10.0	10	20	100
G9B85911	R2.0	10.0	10	20	100
G9B85912	R2.5	10.0	10	20	100
G9B85120	R0.5	12.0	12	24	100
G9B85913	R1.0	12.0	12	24	100
G9B85914	R1.5	12.0	12	24	100
G9B85915	R2.0	12.0	12	24	100
G9B85916	R2.5	12.0	12	24	100

Mill Dia. Tolerance(mm)	Shank Dia. Tolerance
0~-0.03	h6

◎ : Excellent ○ : Good

Carbon Steels	Alloy Steels	Prehardened Steels	Hardened Steels	High Hardened Steels	Copper	Graphite	Cast Iron	Aluminum	Stainless Steels	Titanium	Inconel
~HB225	HB225~325	HRC30~40	HRc40~45 HRc45~55	HRc55~70							
◎	◎	◎			○		○	○	○	○	○





K-2 CARBIDE END MILLS

RECOMMENDED CUTTING CONDITIONS EMPFOHLENE SCHNEIDKONDITIONEN

CARBIDE, 2 FLUTE CORNER RADIUS FINISH SLOTTING VOLLHARTMETALL, 2 SCHNEIDEN ECKENRADIUS SCHLICHTEN NUTENFRÄSEN

G9B82, G9B83 SERIES

MATERIAL	NON-ALLOYED STEELS ALLOY STEELS TOOL STEELS		ALLOY STEELS, HEAT RESISTANT STEELS		STAINLESS STEELS		CAST IRON		ALUMINUM ALLOYS		COPPER, BRASS NON-FERROUS METALS	
HARDNESS	~ HRc 30		HRc 30 ~ HRc 45									
STRENGTH	~1000N/mm ²		1000~1500N/mm ²									
DIAMETER	RPM	FEED	RPM	FEED	RPM	FEED	RPM	FEED	RPM	FEED	RPM	FEED
1.0	14300	105	8500	65	7150	50	18700	205	44000	330	24700	200
1.5	9350	150	5550	85	5600	80	12100	205	27500	385	20300	300
2.0	7850	160	5150	100	4300	80	9350	220	22000	460	16500	340
3.0	6100	180	3800	120	3150	100	6050	220	15400	460	11000	340
4.0	5150	255	3150	155	2650	130	4600	220	11000	460	8800	340
5.0	4300	270	2550	160	2150	135	3650	220	9150	460	6800	340
6.0	3800	300	2300	190	1950	155	2950	255	7600	485	5700	375
8.0	2850	325	1700	170	1450	155	2200	275	5700	485	4400	375
10.0	2200	280	1350	135	1150	135	1850	285	4600	485	3400	375
12.0	1850	240	1150	110	950	110	1450	295	3750	485	2850	375





※ The FEED, in long & extra long types, should be reduced by around 50%

RPM = rev./min. FEED = mm/min.

CARBIDE, 4 FLUTE CORNER RADIUS FINISH SIDE CUTTING VOLLHARTMETALL, 4 SCHNEIDEN ECKENRADIUS SCHLICHTEN SEITENFRÄSEN

G9B84, G9B85 SERIES

MATERIAL	NON-ALLOYED STEELS ALLOY STEELS TOOL STEELS		ALLOY STEELS, HEAT RESISTANT STEELS		STAINLESS STEELS		CAST IRON		ALUMINUM ALLOYS		COPPER, BRASS NON-FERROUS METALS	
HARDNESS	~ HRc 30		HRc 30 ~ HRc 45									
STRENGTH	~1000N/mm ²		1000~1500N/mm ²									
DIAMETER	RPM	FEED	RPM	FEED	RPM	FEED	RPM	FEED	RPM	FEED	RPM	FEED
1.0	17600	150	10250	85	8650	75	18700	620	44000	1050	24700	605
1.5	11800	215	7050	115	7050	120	12100	620	27500	1160	20300	910
2.0	9850	240	6450	145	5350	120	9350	640	22000	1320	16500	1035
3.0	7600	270	4750	170	3950	145	6050	640	15400	1320	11000	1035
4.0	6450	485	3950	300	3300	240	4600	640	11000	1320	8800	1035
5.0	5350	510	3200	305	2700	255	3650	640	9150	1320	6800	1035
6.0	4750	560	2850	350	2400	280	2950	770	7600	1430	5700	1100
8.0	3550	605	2150	325	1800	300	2200	815	5700	1430	4400	1100
10.0	2750	520	1700	255	1450	255	1850	860	4600	1430	3400	1100
12.0	2350	440	1450	215	1150	205	1450	900	3750	1430	2850	1100



※ The FEED, in long & extra long types, should be reduced by around 50%

RPM = rev./min. FEED = mm/min.